



TECHNICAL DATA

A division of Spectrum Organic Products, Inc

Product Name: **Canola Oil, Organic**
 Source: Organically certified Canola seed (*Brassica napus*)
 Manufacturing: Expeller Pressed, organically bleached, deodorized

Canola oil's saturated fat content is one of the lowest of any of the culinary oils in use today. This excellent and versatile oil can be used in most culinary applications requiring a cooking or salad oil.

<u>Property</u>	<u>Typical Analysis</u>	<u>Method</u>
Appearance	Clear	Observation
Organoleptic	Bland Oil	Sensory Evaluation
Color (Lovibond)	≤15Y, 2.0R	AOCS Cc 13b-45, 5¼ cell
Moisture	≤ 0.1%	AOCS Ca 2e-84
Specific Gravity	0.910 to 0.920	AOCS Cc 10a-25 @ 20°C
Free Fatty Acid	≤ 0.1	AOCS Ca 5a-40, as % Oleic Acid
Peroxide Value Initial	≤ 2.0	AOCS Cd 8-53 as meq/kg
Iodine Value	105 to 115	AOCS Cd 1d-92
Saponification Value	182 to 193	AOCS Cd 3-25
Smoke Point	240°C (464°F)	AOCS Cc 9a-48
AOM to 100 meq/kg	20 hr	AOCS Cd-12-57

Typical Fatty Acid Profile (%) AOCS Ce 1e-91

C16:0	Palmitic	3 to 6
C18:0	Stearic	≤3.0
C18:1	Oleic	56 to 66
C18:2	Linoleic	14 to 28
C18:3	Linolenic	4 to 10
C22:1	Erucic	<2.0

Packaging and Storage: Store in a cool dry place (50 to 68 degrees F optimum) away from direct sources of sunlight, heat and oxidizers. Properly stored unopened containers have an expected shelf life of 24 months from date of production.

<u>Item Number</u>	<u>Size</u>	<u>Container Description</u>
120570	420 lb	Closed head food grade lined steel drum, top openings are 2" and ¾" National Coarse Thread, no side bung.
130570	35 lb	Plastic jug in protective carton, available in full pallet loads only, 60 units per pallet.
101570	2019 lb	Disposable tote bin, cardboard shell with plastic liner. Packaged to firm order only. (Tanker truck, appx. 48,000 lbs, may be available by prior agreement.)

This information is furnished without warranty expressed or implied, except that it is accurate to the best knowledge of the Company and is based on information considered to be reliable. Since the conditions of handling and use are beyond our control, we make no guarantee of results or performance of the material and assume no responsibility for damages incurred by use of this material.

5341 Old Redwood Highway, Ste 400 Petaluma, CA 94954 - Phone: 707 778-8900 Fax: 707 765-8738