



# TECHNICAL DATA

A division of Spectrum Organic Products, Inc

Product Name: **Safflower Oil, High Oleic, Organic**  
 Source: Organically certified Safflower seed (*Carthamus tinctorius*)  
 Manufacturing: Expeller Pressed, organically bleached, deodorized

High oleic safflower oil is used for its high resistance to oxidation and heat degradation enabling many culinary applications including high temperature frying. The high monounsaturated fatty acid level is a health benefit.

<u>Property</u>	<u>Typical Analysis</u>	<u>Method</u>
Appearance	Clear	Observation
Organoleptic	Bland Oil	Sensory Evaluation
Color (Lovibond)	≤15Y, 1.2R	AOCS Cc 13b-45, 5¼ cell
Moisture	≤0.05%	AOCS Ca 2e-84
Specific Gravity	0.900 to 0.925	AOCS Cc 10a-25 @ 20°C
Free Fatty Acid	≤0.2	AOCS Ca 5a-40, as % Oleic Acid
Peroxide Value Initial	≤3.0	AOCS Cd 8-53 as meq/kg
Iodine Value	87 to 93	AOCS Cd 1d-92
Saponification Value	185 to 198	AOCS Cd 3-25
Smoke Point	225 °C (437 °F)	AOCS Cc 9a-48
AOM to 100 meq/kg	38.5 hr	AOCS Cd-12-57

**Typical Fatty Acid Profile (%)** AOCS Ce 1e-91

C16:0	Palmitic	4 to 6
C18:0	Stearic	≤3
C18:1	Oleic	75 to 80
C18:2	Linoleic	12 to 16
C18:3	Linolenic	≤1

**Packaging and Storage:** Store in a cool dry place (50 to 68 degrees F optimum) away from direct sources of sunlight, heat and oxidizers. Properly stored unopened containers have an expected shelf life of 24 months.

<u>Item Number</u>	<u>Size</u>	<u>Container Description</u>
120785	420 lb	Closed head food grade lined steel drum, top openings are 2" and ¾" National Coarse Thread, no side bung.
101785	2019 lb	Disposable tote bin, cardboard shell with plastic liner. Packaged to firm order only. (Tanker truck, appx. 48,000 lbs, may be available by prior agreement.)

This information is furnished without warranty expressed or implied, except that it is accurate to the best knowledge of the Company and is based on information considered to be reliable. Since the conditions of handling and use are beyond our control, we make no guarantee of results or performance of the material and assume no responsibility for damages incurred by use of this material.

**5341 Old Redwood Highway, Ste 400 Petaluma, CA 94954 - Phone: 707 778-8900 Fax: 707 765-8738**