



# TECHNICAL DATA

A division of Spectrum Organic Products, Inc

Product Name: **Flax Oil, SpectraVac Organic**  
 Source: Organically certified Flaxseed (*Linum usitatissimum*)  
 Manufacturing: Expeller Pressed under inert gas

Flaxseed oil is valued for its health benefit, the highest content of omega-3 fatty acids from a plant source. Spectrum's unique patented processing technology, SpectraVac (which eliminates damaging oxygen and light), provides the finest flavor-stable flaxseed oil on the market.

<u>Property</u>	<u>Typical Analysis</u>	<u>Method</u>
Appearance	Clear, no sediment	Observation
Organoleptic	Neutral-Nutty, slight fatty	Sensory Evaluation
Color (Lovibond)	48 Y, 5.0 R	AOCS Cc 13b-45, 5¼ cell
Moisture	≤0.5%	AOCS Ca 2e-84
Specific Gravity	0.931	AOCS Cc 10a-25 @ 20°C
Free Fatty Acid	≤1.0	AOCS Ca 5a-40, as % Oleic Acid
Peroxide Value	≤4.0	AOCS Cd 8-53 as meq/kg
Iodine Value	190 - 202	AOCS Cd 1d-92
Saponification Value	191	AOCS Cd 3-25

**Typical Fatty Acid Profile (%)** AOCS Ce 1e-91

C16:0	Palmitic	4 to 6
C18:0	Stearic	≤4
C18:1	Oleic	16 to 23
C18:2	Linoleic	13 to 18
C18:3	Linolenic	51 to 59

**Packaging and Storage:** Store in a cool dry place (50 to 68 degrees F optimum) away from direct sources of sunlight, heat and oxidizers. Properly stored unopened containers have an expected shelf life of 12 months.

<u>Item Number</u>	<u>Size</u>	<u>Container Description</u>
120401	430 lb	Closed head food grade lined steel drum, 2" and ¾" (national coarse thread) opening in lid, no side bung.
105480	1000mg	Bulk gelatin capsules in boxes of 6000 each

This information is furnished without warranty expressed or implied, except that it is accurate to the best knowledge of the Company and is based on information considered to be reliable. Since the conditions of handling and use are beyond our control, we make no guarantee of results or performance of the material and assume no responsibility for damages incurred by use of this material.

**5341 Old Redwood Highway, Ste 400 Petaluma, CA 94954 - Phone: 707 778-8900 Fax: 707 765-8738**